





High Definition Audio

LifeSize[®] Phone[™] is the High Definition audio conference phone that delivers a revolutionary level of quality to audio conferencing.

Better Input. Powered by 16 always-on microphones and patent-pending Circular Microphone Array[™] and beam forming technology, LifeSize Phone provides exceptional room coverage over other phones.

Expand the coverage so everyone can be heard

Better Algorithms. True CD quality, super wide-band audio operates up to 16 kHz frequency using MPEG-4 AAC, the same algorithm used in the popular iPod[®] and iTunes[®] products.

Better Output. Using a specially designed titanium speaker driver and tuned ported enclosure, LifeSize Phone reduces unwanted noise and distortion by up to 10X over any other conference phone—and no need for a subwoofer.

Flexible Connectivity. LifeSize Phone provides Voice over IP (VoIP) audio conferencing and integration to a host of Enterprise-class IP-PBX systems. Also, use LifeSize Phone as a fully integrated audio solution with LifeSize[®] Room[™] and LifeSize[®] Team[™] video systems.

Hear and understand everyone. No more conference fatigue. LifeSize Phone sets the new standard in productive conferencing. Clearly.

The Advantages are Clear

Complete Room Coverage — Pick up all talkers in the room without unwanted noise. Innovative design with 16 omnidirectional microphones and exclusive Circular Microphone Array provides a superior approach to gated, directional microphone devices

Super Wide-Band, Up to 16 kHz Audio — World's best frequency response from 100 Hz up to 16 kHz for highly intelligible conferencing

Standards Compliant — Works with standard SIP or H.323 IP PBX or IP service provider implementation

Low Distortion and Ambient Noise — Designed to reduce noise from HVAC, projector fans for sensitive microphone or talker pickup without the noise

Elegant, **Non-Intrusive Design** — Updated design and no additional microphone pods or sub woofers required.

Simple to Use — Intuitive keypad and display, add a third participant at the touch of a button

Investment Projection — Software-based, remotely upgradable device.

Product Specifications

Phone Console Specifications System Speaker

Specially designed titanium speaker driver 1/4 liter tuned ported speaker enclosure Typical frequency response: 100 Hz to 16 kHz for stand alone phone with IP connection

Distortion: <0.5% 400 Hz - 20 kHz <2% 100 Hz - 400 Hz

Volume: adjustable to 90dBA spl @ .5m No sub-woofer required

System Microphones

Circular Microphone Array with 16 embedded microphones and beam forming with Directivity Index (DI) greater than 4 for all audio frequencies No microphone pods required

Display

Large monochromatic LCD display 240 x 64 pixels; .250 mm pitch



Keypad Intuitive keypad

Network

VoIP connectivity or video systems integration in one device

Audio Standards

G.711; G.722; G.722.1c (Polycom[®] Siren14[™]); G.729; MPEG-4 AAC SIP: RFC 3261; 3264; 2833

Network Configuration Options

IP Configurations

- Standard SIP or H.323 IP PBX or IP service provider implementation To access supported implementations:
- www.lifesize.com/support



005

Packet loss concealment Jitter buffer granularity of 1ms AEC echo tail of >100 ms

No Mobile Phone or PDA Interference

Designed to reduce or eliminates radio frequency interference when placed adjacent to LifeSize Phone

Systems Management & Maintenance

Web browser management for setup and usage Inventory and remote management using SNMPv3 LifeSize® Control[™] management software on IP network



System Design

Physical Dimensions Height: 40.89 mm / 1.61 in Diameter: 286.29 mm / 11.27 in Weight: 1.34 Kg / 3 lbs

Environmental Data

Operating temperature: 0°C (32°F) to 40°C (104°F) Operating humidity: 10% to 85%, non-condensing Storage temperature: -40°C (-40°F) to 70°C (158°F) Storage humidity: 10% to 90%

LifeSize Phone Package

Tabletop console Quick start guide Cables: 1-30 ft. (9.14m) RJ-45 cable to Speakerphone Console Power over Ethernet (PoE) enabled, 802.3af PoE Adapter not included. For recommendations, visit: www.lifesize.com/support

Lifesize Phone is available worldwide in multiple languages.

For additional information: www.lifesize.com/support

Information contained in this document is subject to change without notice. LifeSize is a registered trademark or trademark of LifeSize Communications in the U.S. and other countries. All other trademarks are property of their respective owners. Copyright 2007. May 2007



Corporate Headquarters: 901 S. Mopac Expressway Building 3, Suite 300 Austin, Texas 78746 USA

Phone: +1 512 347 9300 Fax: +1 512 347 9301 Email: info@lifesize.com www.lifesize.com

EMEA: LifeSize Communications United Kingdom Phone: 008000 999 09 799

APAC:

LifeSize Communications Hong Kong Phone: +852 8239 3695